

06/30/99

15674 US

BUCKET: CU-1962 RJS

Assistant Commissioner for Patents
Patent Application
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

Inventor: In Cheol PARK et al
Title: REFLECTIVE LIQUID CRYSTAL DISPLAY OF HIGH APERTURE RATIO,
HIGH TRANSMITTANCE AND WIDE VIEWING ANGLE

Enclosed are the following papers and documents required for filing date under 37 CFR 1.53(b):

- ☒ 19 Pages of specification
- ☒ 7 Pages of claim(s)
- ☒ 1 Pages of abstract
- ☒ 12 Sheets of drawing
- ☒ X Combined Declaration and Power of Attorney
- ☒ X An assignment of the invention to: Hyundai Electronics Industries Co., Ltd.
- ☒ X A certified copy of a Korean (1998-25783) application
- ☒ X Verified Statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- ☒ X Assignment Recordation Cover Sheet with accompanying fee
- ☒ X Other: Appointment of Associate Attorney

The filing fee has been calculated as shown below:

	(Col. 1)	(Col. 2)
FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	3120=	11
INDEP CLAIMS	3-3=	0
<input type="checkbox"/> MULTIPLE DEPENDENT CLAIM PRESENTED		

*If the difference in Col. 1 is less than zero, enter "0"
in Col. 2

SMALL ENTITY			OTHER THAN A SMALL ENTITY		
RATE	FEE	OR	RATE	FEE	
	\$380.	OR		\$760.	
x 9.	\$	OR	x 18.	\$ 198.	
x 39.	\$	OR	x 78.	\$ -	
+ 130.	\$	OR	+ 260.	\$ -	
TOTAL	\$	OR	TOTAL	\$958.	

☒ A check in the amount of \$ 958.00 to cover the filing fee is enclosed.

☒ The Commissioner is hereby authorized to charge payment of any additional filing fees associated with this communication, or credit any overpayment to our Deposit Account No. 12-0400. A duplicate copy of this sheet is attached.

June 30, 1999

Date

Respectfully submitted,

Attorney for Applicant(s)

RICHARD J. STREIT
LADAS & PARRY
224 SOUTH MICHIGAN AVENUE
CHICAGO, ILLINOIS 60604
Reg. No. 25765 (312) 427-1300

"EXPRESS MAIL" mailing label number
Date of Deposit: June 30, 1999
I hereby certify that this paper or fee is being deposited with The United States Postal Service "Express Mail Post Office To Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to Commissioner of Patents and Trademarks, Washington, D.C. 20231
In Cheol Park et al
(Name of applicant, assignee, or Registered Rep.)
Debra M. Szumowski
(Name of person mailing paper or fee)
(Signature of person mailing paper or fee)

L033634099

15674 US
09/345270
06/30/99

**REFLECTIVE LIQUID CRYSTAL DISPLAY
OF HIGH APERTURE RATIO, HIGH TRANSMITTANCE
AND WIDE VIEWING ANGLE**

FIELD OF THE INVENTION

The present invention generally relates to a reflective liquid crystal display(LCD) and more particularly to a reflective LCD having high aperture ratio, high transmittance and wide viewing angle.

BACKGROUND OF THE INVENTION

The reflective LCD generally uses natural light as a light source rather than additional light source such as back-light.

The theory of the reflective LCD can be summarized by that a natural light is radiated from an upper substrate, and then the light is reflected via a reflecting plate disposed at a bottom position of a lower substrate, at this time, the light is absorbed or transmitted depending on the arrangement of liquid crystal molecules.

Most common twisted nematic(TN) mode reflective LCD has the drawback of narrow viewing angle. Therefore, conventionally the hybrid mode reflective LCD capable of displaying full color and having a fast response time in the low voltage condition has been suggested. However, the hybrid mode reflective LCD only uses the birefringence effect of the liquid crystal molecules, accordingly the contrast ratio is degraded since the gray scale inversion is easily occurred depending on the viewing direction. To solve foregoing problem, a bi-axial compensating film is applied to the hybrid mode reflective LCD. However, the bi-axial compensating film is difficult to produce.

Therefore, conventionally the reflective LCD without using any optical compensating film has been suggested to solve the problem of gray scale inversion and to obtain wide viewing angle.

As shown in Figs. 1A and 1B, the reflective LCD comprises a lower substrate 11, an upper substrate 12 opposite to the lower substrate 11, a pixel electrode 13 formed on the lower substrate 11 in the form of strip, a counter electrode 14 formed at the same plane with the pixel electrode 13 and spaced apart by a selected distance, a first homeotropic alignment layer 19 coated on the upper substrate 12, a second homeotropic alignment layer 20 to cover the lower substrate 11 where the pixel electrode 13 and the counter electrode 14, and a liquid crystal layer 15 sandwiched between the first and second homeotropic alignment layers 19,20. Herein, although not shown in the drawing, a color filter is provided at an inner surface of the upper substrate 12.

The reflective LCD further comprises a reflecting plate 16 disposed at an outer surface of the lower substrate 11, a polarizing plate 18 disposed at the backside of the upper substrate 11 and a quarter wave plate 17 disposed between the upper substrate 11 and the polarizing plate 18. Herein, liquid crystal molecules of positive dielectric anisotropy are used for the liquid crystal layer 15. The polarizing plate 18 is disposed such that its polarizing axis makes 45 degrees with the direction of an electric field, and the quarter wave plate 17 is disposed such that its axis makes 45 degrees with the polarizing axis of the polarizing plate 18. Herein, the pixel electrode 13 can be made of an opaque material such as Al or Cr.

Operation of the reflective LCD as constituted above is as follows.

When no voltage is applied to the device, as shown in Figs. 1A and 2A, all the liquid crystal molecules 15a of the liquid crystal layer 15 are arranged such that their long axes are perpendicular to faces of the substrates 11,12 according to the homeotropic alignment layers 19,20. Then this, light of a selected direction among not-polarized light of the light source is linearly-polarized in the left or right via the polarizing plate 18. Once the light passing the polarizing plate 18 passes the quarter wave plate 17, the light is left-

circularly-polarized or right-circularly-polarized. Since all the liquid crystal molecules 15a in the liquid crystal layer 15 are arranged in the z direction, the light passed the quarter wave plate 17 directly passes through the liquid crystal layer 15 without causing any phase difference in the light. The light arrived at the reflecting plate 16 changes its transmitting direction into the -z direction. Accordingly, before the left(or right)-circularly-polarized light is reflected, the light is right(or left)-circularly-polarized. The right(or left)-circularly-polarized light directly passes the liquid crystal display 15 and the light is radiated into the quarter wave plate 17 again. The light passed through the quarter wave plate 17 is left(or right)-linearly-polarized. However, since an axis of the light passed through the polarizing plate 18 is perpendicular to an axis of the light radiated to the polarizing plate 18, the light radiated from the quarter wave plate 17 to the polarizing plate 18 does not pass the polarizing plate 18. Accordingly, the screen shows dark state.

On the other hand, when voltage is applied to the device as shown in Figs. 1B and 2B, the liquid crystal molecules 15a directly in contact with the substrates hold their arrangement same as when no voltage is applied to the device according to an influence of the homeotropic alignment layers 19,20. In the respective central regions of the pixel electrode 13 and the counter electrode 14 similar to the case when no voltage is applied thereto, long axes of the liquid crystal molecules 15a are arranged perpendicular to faces of the upper substrate 12 and the lower substrate 11. Since there is formed a horizontal electric field E_1 and an elliptic electric field E_2 between the pixel electrode 13 and the counter electrode 14, the liquid crystal molecules are arranged according to electric fields E_1, E_2 . Accordingly, there are formed two domains forming a symmetry in their left side and right side with respect to the center line of the pixel electrode 13 and the counter electrode 14 except the region in contact with the substrates 11,12.

With regard to the light transmitting process, light of a selected direction among not-polarized light of the light source is linearly-polarized by passing through the polarizing plate 18. Once the light passes the quarter wave plate 17, the linearly-polarized light is changed to be left(or right)-circularly-polarized. According to the angle between the optical axes of the liquid crystal molecules and a transmitting axis of the quarter wave plate 17, the light changes its polarizing state while passing the liquid crystal layer 15. That is to say, the left-circularly-polarized light is left-linearly-polarized while passing the liquid crystal layer 15 and the light is left(or right)-linearly-polarized again. The light reflected from the reflecting plate 16 is right(or left)-linearly-polarized. The right(or left)-circularly-polarized light is left(or right)-circularly-polarized while passing again the liquid crystal layer 15. Afterward, the left(or right)-circularly-polarized light is radiated into the quarter wave plate 17. The light passed through the quarter wave plate 17 is right(or left)-linearly-polarized. Consequently, the axis of the polarizing plate 18 is coincided with the optical axis passed through the quarter wave plate 17. Accordingly, the screen shows white state.

To form an in-plane electric field E_1 and an elliptic electric field E_2 as described above, the distance ℓ between the electrodes 13,14 should be set relatively larger than the cell gap d , and widths of the respective electrodes 13,14 should be set relative wider, for example in the range of $10 \sim 20 \mu\text{m}$ to obtain a selected degree of intensity of electric field. However, when the device has a constitution as described above, although an electric field almost parallel to the substrate is formed between the electrodes 13,14, there are occurred equipotential lines in the upper portions of the electrodes 13,14 since most of the upper portions of the electrodes 13,14 are not affected by the electric field. As a result, the transmittance is degraded greatly.

SUMMARY OF THE INVENTION

Accordingly, it is the object of the present invention to provide a reflective LCD capable of improving the transmittance and aperture ratio by transmitting light into
5 the upper portions of the electrodes.

To accomplish the foregoing object, the present invention provides a reflective LCD comprising:

a lower substrate and an upper substrate opposed with a selected distance;

10 a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules;

a gate bus line and a data bus line formed on the lower substrate to define a pixel;

15 a counter electrode and a pixel electrode formed at an inner surface of the lower substrate, wherein both electrodes are formed with a selected distance and width so that most of the liquid crystal molecules in upper portions of those electrodes are sufficiently driven by forming a fringe field
20 between said counter and pixel electrodes;

a thin film transistor provided adjacent to an intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected;

25 a polarizing plate disposed at an outer surface of the upper substrate;

a reflecting plate disposed at an outer surface of the lower substrate; and

30 a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate,

wherein both counter and pixel electrodes are made of a transparent conductor,

35 wherein a distance between the upper and lower substrates is greater in length than a distance between the counter and pixel electrodes.

The present invention further provides a reflective LCD comprising:

a lower substrate and an upper substrate opposed with a first distance;

5 a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules;

a gate bus line and a data bus line formed on the lower substrate to define a pixel;

10 a counter electrode formed at each pixel of the lower substrate, transmitted with the common signal and having a plurality of branches diverged in parallel with the data bus line and at least a bar for connecting the branches, wherein the respective branches have a first width and they are spaced with a second distance;

15 a pixel electrode having a plurality of strips formed between the respective branches of the counter electrode, having a second width, and spaced apart by a third distance, and at least a bar for connecting the strips;

20 a thin film transistor provided adjacent to an intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected;

25 a polarizing plate disposed at an outer surface of the upper substrate;

a reflecting plate disposed at an outer surface of the lower substrate; and

30 a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate,

wherein both counter and pixel electrodes are made of a transparent conductor,

35 wherein the first distance is greater in length than a distance between the branch of the counter electrode and the strip of the pixel electrode,

wherein the first and second widths are set such that the liquid crystal molecules in upper portions of the branch

of the counter electrode and the strip of the pixel electrode are all aligned by the electric field between adjacent branches and strips.

5 Moreover, the present invention provides a reflective LCD comprising:

 a lower substrate and an upper substrate opposed with a selected distance;

10 a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules;

 a gate bus line and a data bus line formed on the lower substrate to define a pixel;

15 a counter electrode formed at each pixel of the lower substrate, transmitted with a common signal and shaped of a plate;

 a pixel electrode formed over the counter electrode and having a plurality of strips, wherein the strip has a selected width and spaced from each other by a selected distance;

20 a thin film transistor provided adjacent to an intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected;

25 a polarizing plate disposed at an outer surface of the upper substrate;

 a reflecting plate disposed at an outer surface of the lower substrate; and

30 a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate,

 wherein both counter and pixel electrodes are made of a transparent conductor,

 wherein a distance between the upper and lower substrates is greater in length than a distance between the counter electrode and the pixel electrode,

 wherein a width of the strip of the pixel electrode and a width of the counter electrode disposed between the strips

are set such that the liquid crystal molecules in upper portions of the counter electrode disposed between the strips and the strip of the pixel electrode are all aligned by the electric field between adjacent branches and strips.

5

In the reflective LCD according to the present invention, it is possible to drive the liquid crystal molecules in upper portions of driving electrodes according to fringe fields being formed at both sides of the electrodes since both counter and pixel electrodes are made of a transparent material and a distance between the driving electrodes is smaller in length than the cell gap so as to form a plurality of fringe fields. Therefore, compared to the conventional IPS mode LCD, the transmittance of LCD device can be greatly improved.

15

BRIEF DESCRIPTION OF THE DRAWINGS

20

Figs. 1A and 1B are cross-sectional views showing a conventional reflective LCD.

Figs. 2A and 2B illustrate light transmitting process in the conventional reflective LCD.

Fig. 3 is a perspective view showing a reflective LCD according to the present invention.

25

Fig. 4 is a plan view showing an LCD according to an embodiment of the present invention.

Figs. 5A to 5D illustrate light transmitting process in the LCD according to the present invention when the electric field is off.

30

Fig. 6 is a cross-sectional view showing the reflective LCD according to the present invention.

Figs. 7A to 7C illustrate light transmitting process in the LCD according to the present invention when the electric field is on.

35

Fig. 8 is a plan view showing another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, detailed description of the preferred
embodiments will be discussed with reference to the attached
5 drawings.

Referring to Figs. 3 and 4, a lower substrate 40 is
opposed to an upper substrate 60 with a selected distance d11.
A liquid crystal layer 65 is sandwiched between the lower
substrate 40 and the upper substrate 60. Liquid crystal
10 molecules 65a in the liquid crystal layer 65 is nematic
molecules. Further, the liquid crystal layer 65 is preferably
formed such that the product of the index of refractive
anisotropy Δn of the liquid crystal molecules 65a and the
cell gap d11 is $0.2 \sim 1.5 \mu\text{m}$. In the meantime, the dielectric
15 anisotropy $\Delta \epsilon$ is set according to an angle between a rubbing
axis and the x-axis. A polarizing plate 70 for linearly-
polarizing a natural light in a selected direction is attached
at an outer surface of the upper substrate 60. A quarter wave
plate 75 for shifting the phase of light passed the liquid
20 crystal layer 65 by 90 degrees, is attached at an outer
surface of the lower substrate 40. A reflecting plate 78 for
reflecting the light passed the quarter wave plate 75 to the
liquid crystal layer 65, is attached at an outer surface of
the quarter wave plate 75. Herein, the quarter wave plate 75
25 can be disposed between the polarizing plate 70 and the upper
substrate 60 as in the conventional LCD.

As shown in Fig. 4, on the lower substrate 40, a
plurality of gate bus lines 41a, 41b are disposed with a
selected interval, arranged and extended in the x direction.
30 Further, a plurality of data bus lines 47a, 47b are disposed on
the lower substrate 40 with a selected interval and extended
in the y direction. As a result, the data bus lines together
with the gate bus lines 41a, 41b define matrix regions. In the
drawings, only a pair of gate bus lines 41a, 41b and a pair of
35 data bus lines 47a, 47b are shown. Herein, the matrix region
comprises a pair of gate bus lines 41a, 41b and a pair of data
bus lines 47a, 47b, and then the matrix region becomes a pixel

of an LCD. Gate insulating layers(not shown) are sandwiched between the gate bus lines 41a,41b and the data bus lines 47a,47b thereby insulating therebetween. A common signal line 42 is extended in a selected direction, for example the x direction and is disposed between a pair of gate bus lines 41a,41b. For instance, preferably the common signal line 42 is disposed close to a previous gate bus line 41a rather than its corresponding gate bus line 41a. Herein, to reduce the RC delay time, the gate bus lines 47a,47b, the common signal line 42 and the data bus lines 47a,47b are made of a metal layer having a high conductivity selected from a group consisting of Al, Mo, Ti, W, Ta, Cr and composition thereof, or made of at least two alloy layers selected from the group. In the present embodiment, MoW alloy layer is used.

A counter electrode 43 is formed within each pixel region of the lower substrate 40. Herein, the counter electrode 43 is formed on the lower substrate 40 and is in contact with the common signal line 42. A selected portion of the counter electrode is connected to the common signal line 42 thereby receiving a common signal. Herein, the counter electrode 43 comprises a body 43a being disposed parallel to the gate bus lines 41a,41b and in contact with the common signal line 42, and a plurality of branches 43b being extended from the body 43a in the y direction. Namely, the counter electrode 43 is formed in the shape of a comb. Herein, the respective branches 43b have a selected width P11 and are spaced each other with a selected distance L11. At this time, the width P11 and the distance L11 of the respective branches 43b are formed a bit narrower than those conventional ones while taking into consideration of width and distance of a pixel electrode to be formed in subsequent processes.

The pixel electrode 46 is also formed within each pixel region of the lower substrate 40. Herein, the pixel electrode 46 is formed on a gate insulating layer 44 so as to overlap the counter electrode 43. The pixel electrode 46 comprises a first part 46a being overlapped with the body 43a of the counter electrode 43, a plurality of second parts 46b being

extended from the first part in the y direction with the form of strip. Herein, the second parts 46b have a selected width P12 and they are spaced with a selected distance L12. Further, the second parts 46b are disposed between the branches 43b of the counter electrode 43.

Herein, although not shown in the drawing, ends of the branches 43b of the counter electrode 43 can be bound with a bar(not shown) being disposed parallel to the gate bus line 41a and ends of the second parts 46b of the pixel electrode 46 can be bound with the bar(not shown) being disposed parallel to the gate bus line 41a. Otherwise, only the ends of the branches 43b of the counter electrode 43 can be bound, or only the ends of the second parts 46b of the pixel electrode 46 can be bound selectively.

In the present embodiment, the width P12 of the second parts 46b of the pixel electrode 46 is formed narrower than the distance L11 between the branches 43b of the counter electrode 43. Accordingly, the second parts 46b of the pixel electrode 46 are spaced from the branches 43b of the counter electrode 43 by a selected distance ℓ 11. At this time, the distance ℓ 11 between the second parts 46b of the pixel electrode 46 and the branches 43b of the counter electrode 43, is formed narrower than the cell gap d11 between two substrates 40,60 and the distance ℓ 11 is set in the range of $0.1\mu\text{m} \sim 5\mu\text{m}$ when the pixel size is $110\mu\text{m} \times 330\mu\text{m}$. The widths of the branches 43b of the counter electrode 43 and the second parts 46b of the pixel electrode 46 are formed such that fringe fields formed therebetween can affect upper portions thereof. For instance, when the size of pixel is $110\mu\text{m} \times 330\mu\text{m}$ and eight branches 43b of the counter electrode 43 and seven second parts 46b of the pixel electrode 46 are formed therein, the widths of the branches 43b and the second parts 46b are set in the range of $1 \sim 8\mu\text{m}$, more preferably in the range of $2 \sim 5\mu\text{m}$. Furthermore, the ratio of the width P12 of the second parts 46b to the width P11 of the branches 43b is in the range of $0.2 \sim 4$.

Herein, width and distance of the branches 43b of the

counter electrode 43 and the second parts 46b of the pixel electrode are adjustable according to the size of pixel and number of the same. However, the widths of those electrodes 43b,46b should be formed such that the liquid crystal molecules in the upper portions of the electrodes are sufficiently driven by the fringe field formed between the electrodes 43b,46b. Herein, The counter electrode 43 and the pixel electrode 46 are made of transparent materials.

A thin film transistor 50 as a means for switching is formed adjacent to the respective intersections of the gate bus lines 41a and the data bus lines 47a. The thin film transistor 50 comprises a channel layer 45 formed on the gate bus line 41a; a drain electrode 48 overlapped with one side of the channel layer 45 and extended from the data bus line 47a; and a source electrode 49 overlapped with the other side of the channel layer 45 and in contact with a selected portion of the pixel electrode 46.

A storage capacitor Cst is occurred at a region that the counter electrode 43 and the pixel electrode 46 are overlapped. The storage capacitor Cst acts for maintaining data signal for one frame. In the present embodiment, the storage capacitor Cst is occurred at the region that the body 43a of the counter electrode 43 and the first part 46a of the pixel electrode 46 are overlapped.

A color filter(not shown) is arranged at the inner surface of the upper substrate 60.

A first alignment layer 53 is formed on the resultant of the lower substrate 40 and a second alignment layer 63 is formed at an inner surface of the color filter of the upper substrate 60. The respective alignment layers 53,63 have surfaces for arranging the liquid crystal molecules(not shown) in a selected direction. Further, the first and second alignment layers 53,63 are treated so that the liquid crystal molecules have a pretilt angle of $0 \sim 10^\circ$. The first alignment layer 53 in the lower substrate 40 is rubbed to make an angle ϕ with the x direction, and the second alignment layer 63 in the upper substrate 52 is rubbed to be anti-

parallel to the rubbing direction of the first alignment layer 53, i.e. to make approximately 180° . At this time, when the x-axis that becomes the electric field forming direction later, and the rubbing direction of the first alignment layer 53 or the second alignment layer 63 make exactly 45° , both liquid crystal molecules of positive and negative dielectric anisotropy can be used. When the x-axis that becomes the electric field forming direction later, and the rubbing axis of the first alignment layer 53(or the second alignment layer 63) make over 45° , the liquid crystal molecules of positive dielectric anisotropy can be used. Otherwise they make below 45° , then the liquid crystal molecules of negative dielectric anisotropy can be used. Herein, the reason different types of molecules are used according to the angle between the rubbing axis of the alignment layer and the x-axis, is that the maximum transmittance of the LCD can be obtained by doing so. A polarizing plate 70 is disposed such that its polarizing axis P is parallel to the rubbing axes of the first alignment layer 53 and the second alignment layer 63.

Operation of the reflective LCD as constituted above will be discussed hereinafter.

First, when the gate bus lines 41a is not selected, no signal is transmitted to the pixel electrode 46b from the data bus line 47a, there is formed no electric field between the counter electrode 43 and the second part 46b of the pixel electrode 46.

Then this, the natural light is linearly-polarized according to the polarizing plate 70. As shown in Fig. 5A, the linearly-polarized-light is coincided with the polarizing axis P of the polarizing plate 70. At this time, Fig. 5A shows a polarizing state of the light, assuming that the light 100 passed through the polarizing plate 70 having the same component in their horizontal and vertical phases and the transmitting direction of the polarized light is the z-axis and the phase of the x component of the transmitted light is faster than that of the y component. The light 100 does not change its polarizing state while passing the liquid crystal

layer 65.

The linearly-polarized light that is passed through the liquid crystal layer 65, changes its polarizing state while passing the quarter wave plate 75. That is to say, the quarter wave plate 75 occurs a phase difference of approximately 90° i.e. a quarter of one period, for example 360° at a normal path and an abnormal path. As a result, referring to Fig. 5B, the linearly-polarized light changes right-circularly-polarized while passing the quarter wave plate 75.

The right-circularly-polarized light that is passed through the quarter wave plate 75, occurs phase difference of 180° according to the reflecting plate 78 thereby left-circularly-polarizing the light reflected by the reflecting plate 78 as shown in Fig. 5C. At this time, by passing the reflecting plate 78, the light transmitting direction is the z-axis. Accordingly, the polarizing axis of the polarizing plate 75 can be looked as P'.

As the light passed the reflecting plate 78 is passed again the quarter wave plate 28, the right-linearly-polarized light is left-circularly-polarized as shown in Fig. 5D.

Then, the left-linearly-polarized light 100 that is passed through the quarter wave plate 75 does not change its polarizing state while passing the liquid crystal layer 65, and the light passed through the liquid crystal layer 65 arrives at the polarizing plate 70. At this time, the polarizing axis p' of the polarizing plate 70 is perpendicular to the left-linearly-polarized light 100 (in Fig. 5D). Accordingly, the light 100 does not pass the polarizing plate 70. The screen shows dark state.

On the other hand, when a scanning signal is transmitted to the gate bus line 41a and a display signal is transmitted to the data bus line 47a, the thin film transistor 50 formed adjacent to the intersection of the gate bus line 41a and the data bus line 47a is turned on thereby transmitting the signals to the pixel electrode 46. At this time, a common signal having a different voltage from the display signal is continuously applied to the counter electrode 43, and there is

formed an electric field E_f between the counter electrode 43 and the pixel electrode 46. Herein, the electric field E_f is substantially formed between the branch 43b of the counter electrode 43 and the second part 46b of the pixel electrode 46.

At this time, the distance ℓ_{11} between the branch 43b of the counter electrode 43 and the second part 46b of the pixel electrode 46 is a bit narrower than the distance between electrodes of the conventional IPS-LCD, therefore as shown in Fig. 6, the electric field is formed as a parabolic fringe field E_f having a larger curvature compared to the electric field of the conventional IPS-LCD. Further, since the widths of the branch 43b of the counter electrode 43 and the second part 46b of the pixel electrode 46 are sufficiently narrow such that the liquid crystal molecules in the upper portions of the electrodes 43,46 are driven by the fringe field E_f . Accordingly, the aperture ratio and transmittance are improved. Furthermore, when the fringe field E_f is projected to the lower substrate 40, the fringe field E_f and rubbing axes of the alignment layers 63,53 make approximately $\pm 45^\circ$. As a result, for example, when liquid crystal molecules 65a of positive dielectric anisotropy is used, long axes of the liquid crystal molecules is parallel with the electric field, and then the long axes of the liquid crystal molecules 65 and the polarizing axis or the rubbing axis make 45° respectively.

This satisfies the maximum transmittance condition.

At this time, the light incident to the LCD device of the present embodiment has a transmitting process as follows.

First of all, it is on the assumption that the natural light is left-linearly-polarized in the same direction that the polarizing axis of the polarizing plate 70, when the light passes the polarizing plate 70 as shown in Fig. 7A. At this time, the light transmitting direction is the direction of z-axis.

Afterward, as shown in Fig. 7B, the light passed through the polarizing plate 70 changes its polarizing state into the right-circularly-polarized state while passing the liquid crystal layer 65. In other words, the liquid crystal molecules

are rearranged according to the electric field E_f , therefore the liquid crystal layer 65 has a phase deference of 90 degrees.

And then, the light 100 passed through the liquid crystal layer 65 is right-linearly-polarized while passing the quarter wave plate 75 having the phase difference of 90 degrees as shown in Fig. 7C.

The light 100 passed through the quarter wave plate 75 occurs a phase shift by 180 degrees while passing the reflecting layer 78. Accordingly, the light 100 is left-linearly-polarized while passing the reflecting plate 78. At this time, the light transmitting direction becomes the -z-axis while passing the reflecting plate 78. Therefore, the direction of polarizing plate P' can be looked.

Next, as shown in Fig. 7E, the light 100 passed through the reflecting plate 78 is right-circularly-polarized while passing the quarter wave plate 75, and then, the right-circularly-polarized light is right-linearly-polarized while passing the liquid crystal layer 65. As a result, the right-circularly-polarized light 100 passed through the liquid crystal layer 65 is coincided with the direction of polarizing plate P' thereby passing the upper polarizing plate 70. The screen shows white state.

Furthermore, a relatively low threshold voltage compared to the conventional one can be obtained by shortening the distance ℓ 11 between the electrodes. Generally the threshold voltage of IPS mode LCD can be expressed as follows.

$$V_{th} = \pi \ell / d (K_2 / \epsilon_0 \Delta \epsilon)^{1/2} \text{----- equation 1}$$

wherein, V_{th} is a threshold voltage,
 ℓ is the distance between the electrodes,
 d is a cell gap,
 K_2 is a modulus of twist elasticity,
 ϵ_0 is a dielectric constant, and
 $\Delta \epsilon$ is an index of dielectric anisotropy.

As shown in the equation 1, according to the present embodiment, the value of l/d is relatively reduced and the threshold voltage is still more lowered. Accordingly, the present embodiment enables the operation in the low voltage condition.

The response time of LCD according to the present embodiment can be greatly improved compared to the conventional LCDs for the following reasons. First, the linear distance of the electric field being formed between the electrodes 43b, 46b is formed greatly shorter than that of the conventional IPS-LCD, thereby intensifying the strength of electric field. Secondly, there is formed a parabolic fringe field having larger curvature and radius compared to the conventional one due to the short distance between the electrodes thereby effectively driving the liquid crystal molecules in the upper substrate.

[Embodiment 2]

Fig. 8 is a plan view showing another embodiment of the present invention. Similar constitution as in the first embodiment is applied to the present embodiment 2 except the shape of a counter electrode. Accordingly, description of the counter electrode will be discussed hereinafter.

Namely, the counter electrode 430 according to the present embodiment, is formed within each pixel region of the lower substrate 40. Herein, the counter electrode 430 is formed at the same plane with the gate bus lines 41a, 41b and is in contact with the common signal line 42. The counter electrode 430 is made of a transparent metal, such as ITO and shaped of a plate, more preferably rectangular plate. Herein, the counter electrode 430 is spaced from the gate bus lines 41a, 41b and the data bus lines 47a, 47b respectively.

The pixel electrode 460 is also formed within each unit pixel region of the lower substrate 40. At this time, the pixel electrode 460 is formed on the gate insulating layer (not shown) so that the pixel electrode 460 is overlapped with the counter electrode 430. Herein, the pixel electrode 460 is made

of a transparent conductive material, for example the ITO metal similar to the counter electrode 430. The pixel electrode 460 also comprises a first part 460a being disposed parallel to the gate bus lines 41a, 41b, i.e. in the x direction, and a plurality of second parts 460b, for example seven second parts 460b being extended from the first part 460a in the y direction in the form of strip. At this time, the first part 460a and the second parts 460b of the pixel electrode 460 are all overlapped with the counter electrode 430. Therefore, the storage capacitance is more increased than the first embodiment.

The respective second parts 460b have a selected width P22 and are spaced apart by a selected distance L22. Further, since the counter electrode 430 is in the form of a plate, the counter electrode 430 is exposed through a distance between the respective second parts 460b of the pixel electrode 460.

At this time, ends of the second parts 460b of the pixel electrode 460 are bounded with a third part having a bar shape.

In a plan view, there seems to be no gap between the second part 460b of the pixel electrode 460 and the counter electrode 430. However, in a sectional view, there exists a distance as much as the thickness of the gate insulating layer (not shown).

When the size of pixel is $110 \times 330 \mu\text{m}$, the distance L22 between the second parts 460b of the pixel electrode 460 and the counter electrode 430 is in the range of approximately 0.2 ~ 5. At this time, the distance L22 can be adjusted according to the size of pixel and the number of second parts 460b. Further, under the same pixel size condition, the ratio of widths P22 of the second parts 460b of the pixel electrode 460 to the distance L22 between the second parts 460b of the pixel electrode 460 is set in the range of 0.2 ~ 5, and the ratio of the distance L22 between second parts 460b of the pixel electrode 460 to the cell gap d11 is set in the range of 0.1 ~ 5.

As described in detail, according to the present invention, following effects can be obtained.

First, in the reflective LCD, both counter and pixel electrodes are made of transparent materials, the distance between the electrodes are narrower than the cell gap so that a plurality of fringe fields may be formed, and the widths of the driving electrodes are formed narrow enough to drive the liquid crystal molecules formed in both sides of the electrodes sufficiently thereby sufficiently driving all liquid crystal molecules in the upper portions of the electrodes. Accordingly, the transmittance of the reflective LCD is greatly improved.

Secondly, an enhanced aperture ratio is obtained since both counter and pixel electrodes are made of a transparent material.

Thirdly, the response time is greatly improved since there is formed a fringe field of large curvature that drives the liquid crystal molecules in the upper substrate due to narrow distance of the counter and pixel electrodes, and the strength of electric field is intensified due to short distance of electrodes.

Fourthly, since the distance of electrodes are shorter than the cell gap, a lower threshold voltage compared to the conventional IPS mode LCD is obtained. Accordingly, the present invention enables the operation in the low voltage condition.

Fifthly, the viewing angle of relatively wider than the conventional TN mode LCD can be obtained.

Sixthly, the size of LCD and manufacturing thereof can be reduced since no extra light source is required.

Various other modifications will be apparent to and can be readily made by those skilled in the art without departing from the scope and spirit of the present invention.

What is claimed is,

1. A reflective liquid crystal display(LCD) of high aperture ratio, high transmittance and wide viewing angle comprising:

a lower substrate and an upper substrate opposed with a selected distance;

a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules;

a gate bus line and a data bus line formed on the lower substrate to define a pixel;

a counter electrode and a pixel electrode formed at an inner surface of the lower substrate, wherein both electrodes are formed with a selected distance and width so that most of the liquid crystal molecules in upper portions of those electrodes are sufficiently driven by forming a fringe field between said counter and pixel electrodes;

a thin film transistor provided adjacent to an intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected;

a polarizing plate disposed at an outer surface of the upper substrate;

a reflecting plate disposed at an outer surface of the lower substrate; and

a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate,

wherein both counter and pixel electrodes are made of a transparent conductor,

wherein a distance between the upper and lower substrates is greater in length than a distance between the counter and pixel electrodes.

2. The reflective LCD of claim 1, wherein the transparent conductor is ITO(indium tin oxide).

3. The reflective LCD of claim 1, further comprising a first alignment layer coated on an opposing face of the lower substrate and having a surface for aligning the liquid crystal molecules in a selected direction in the absence of electric field and having a first rubbing axis which makes a selected angle with the electric field, and a second alignment layer coated on an opposing face of the upper substrate and having a surface for aligning the liquid crystal molecules in a selected direction in the absence of electric field and having a second rubbing axis which makes a selected angle with the first rubbing axis.

4. The reflective LCD of claim 3, wherein the first and second alignment layers are given with a pretilt angle of 0 ~ 10 degrees.

5. The reflective LCD of claim 4, wherein those rubbing axes of the first and second alignment layers are disposed anti-parallel each other.

6. The reflective LCD of claim 5, wherein the polarizing axis of the polarizing plate is coincided with the second rubbing axis.

7. The reflective LCD of claim 6, wherein the liquid crystal molecules of negative dielectric anisotropy is used when the angle between the second rubbing axis and the electric field is 0~45 degrees, and the liquid crystal molecules of positive dielectric anisotropy is used when the angle between the second rubbing axis and the electric field is 45 ~ 90 degrees.

8. The reflective LCD of claim 1, wherein the product of refractive anisotropy of the liquid crystal molecules and the distance between the upper and lower substrates is 0.2 ~ 0.6 μm .

9. A reflective LCD of high aperture ratio, high transmittance and wide viewing angle comprising:

a lower substrate and an upper substrate opposed with a first distance;

5 a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules;

a gate bus line and a data bus line formed on the lower substrate to define a pixel;

10 a counter electrode formed at each pixel of the lower substrate, transmitted with the common signal and having a plurality of branches diverged in parallel with the data bus line and at least a bar for connecting the branches, wherein the respective branches have a first width and they are spaced with a second distance;

15 a pixel electrode having a plurality of strips formed between the respective branches of the counter electrode, having a second width, and spaced apart by a third distance, and at least a bar for connecting the strips;

20 a thin film transistor provided adjacent to an intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected;

25 a polarizing plate disposed at an outer surface of the upper substrate;

a reflecting plate disposed at an outer surface of the lower substrate; and

30 a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate,

wherein both counter and pixel electrodes are made of a transparent conductor,

35 wherein the first distance is greater in length than a distance between the branch of the counter electrode and the strip of the pixel electrode,

wherein the first and second widths are set such that the liquid crystal molecules in upper portions of the branch

of the counter electrode and the strip of the pixel electrode are all aligned by the electric field between adjacent branches and strips.

5 10. The reflective LCD of claim 9, wherein the transparent conductor is ITO(indium tin oxide).

11. The reflective LCD of claim 9, wherein the second width is smaller in length than the second distance, and the
10 first width is smaller in length than the third distance.

12. The reflective LCD of claim 11, wherein the distance between the branch of the counter electrode and the strip of the pixel electrode is in the range of 0.1 ~ 5 μm .

13. The reflective LCD of claim 11, wherein the width ratio of the second width to the first width is 0.2 ~ 5.

14. The reflective LCD of claim 13, wherein the lengths
20 of the first width and the second width are in the range of 2 ~ 8 μm respectively.

15. The reflective LCD of claim 9, further comprising a first alignment layer coated on an opposing face of the lower substrate and having a surface for aligning the liquid crystal molecules in a selected direction in the absence of electric field and having a first rubbing axis which makes a selected angle with the electric field, and a second alignment layer coated on an opposing face of the upper substrate and having a
25 surface for aligning the liquid crystal molecules in a selected direction in the absence of electric field and having a second rubbing axis which makes a selected angle with the
30 first rubbing axis.

16. The reflective LCD of claim 15, wherein the first and second alignment layers are given with a pretilt angle of 0 ~ 10 degrees.

17. The reflective LCD of claim 16, wherein those rubbing axes of the first and second alignment layers are disposed anti-parallel each other.

18. The reflective LCD of claim 17, wherein the polarizing axis of the polarizing plate is coincided with the second rubbing axis.

19. The reflective LCD of claim 18, wherein the liquid crystal molecules of negative dielectric anisotropy is used when the angle between the second rubbing axis and the electric field is $0 \sim 45$ degrees, and the liquid crystal molecules of positive dielectric anisotropy is used when the angle between the second rubbing axis and the electric field is $45 \sim 90$ degrees.

20. The reflective LCD of claim 1, wherein the product of refractive anisotropy of the liquid crystal molecules and the first distance is $0.2 \sim 0.6 \mu\text{m}$.

21. A reflective LCD of high aperture ratio, high transmittance and wide viewing angle comprising:

a lower substrate and an upper substrate opposed with a selected distance;

a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules;

a gate bus line and a data bus line formed on the lower substrate to define a pixel;

a counter electrode formed at each pixel of the lower substrate, transmitted with a common signal and shaped of a plate;

a pixel electrode formed over the counter electrode and having a plurality of strips, wherein the strip has a selected width and spaced from each other by a selected distance;

a thin film transistor provided adjacent to an

intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected;

5 a polarizing plate disposed at an outer surface of the upper substrate;

a reflecting plate disposed at an outer surface of the lower substrate; and

10 a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate,

wherein both counter and pixel electrodes are made of a transparent conductor,

15 wherein a distance between the upper and lower substrates is greater in length than a distance between the counter electrode and the pixel electrode,

20 wherein a width of the strip of the pixel electrode and a width of the counter electrode disposed between the strips are set such that the liquid crystal molecules in upper portions of the counter electrode disposed between the strips and the strip of the pixel electrode are all aligned by the electric field between adjacent branches and strips.

25 22. The reflective LCD of claim 21, wherein the transparent conductor is ITO(indium tin oxide).

23. The reflective LCD of claim 21, wherein the ratio of a width of the respective strips of the pixel electrode to a distance of the strips is 0.2 ~ 5.

30 24. The reflective LCD of claim 23, wherein the widths of the respective strips is in the range of 1 ~ 8 μ m respectively.

35 25. The reflective LCD of claim 23, wherein the ratio of the distance of the respective strips of the pixel electrode to the distance between the upper and lower substrates is 0.1 ~ 5.

26. The reflective LCD of claim 23, further comprising a first alignment layer coated on an opposing face of the lower substrate and having a surface for aligning the liquid crystal molecules in a selected direction in the absence of electric field and having a first rubbing axis which makes a selected angle with the electric field, and a second alignment layer coated on an opposing face of the upper substrate and having a surface for aligning the liquid crystal molecules in a selected direction in the absence of electric field and having a second rubbing axis which makes a selected angle with the first rubbing axis.

27. The reflective LCD of claim 26, wherein the first and second alignment layers are given with a pretilt angle of 0 ~ 10 degrees.

28. The reflective LCD of claim 27, wherein those rubbing axes of the first and second alignment layers are disposed anti-parallel each other.

29. The reflective LCD of claim 28, wherein the polarizing axis of the polarizing plate is coincided with the second rubbing axis.

30. The reflective LCD of claim 29, wherein the liquid crystal molecules of negative dielectric anisotropy is used when the angle between the second rubbing axis and the electric field is 0 ~ 45 degrees, and the liquid crystal molecules of positive dielectric anisotropy is used when the angle between the second rubbing axis and the electric field is 45 ~ 90 degrees.

31. The reflective LCD of claim 21, wherein the product of refractive anisotropy of the liquid crystal molecules and the first distance is 0.2 ~ 0.6 μm .

ABSTRACT OF DISCLOSURE

Disclosed is a reflective liquid crystal display. The present invention provides a reflective liquid crystal display comprising: a lower substrate and an upper substrate opposed with a selected distance; a liquid crystal layer sandwiched between the lower and upper substrates and comprising a plurality of liquid crystal molecules; a gate bus line and a data bus line formed on the lower substrate to define a pixel; a counter electrode and a pixel electrode formed at an inner surface of the lower substrate, wherein both electrodes are formed with a selected distance and width so that most of the liquid crystal molecules in upper portions of those electrodes are sufficiently driven by forming a fringe field between said counter and pixel electrodes; a thin film transistor provided adjacent to an intersection of the gate bus line and the data bus line and transmitting a signal of the data bus line into the pixel electrode when the gate bus line is selected; a polarizing plate disposed at an outer surface of the upper substrate; a reflecting plate disposed at an outer surface of the lower substrate; and a quarter wave plate sandwiched between the quarter wave plate and the lower substrate, or between the polarizing plate and the upper substrate, wherein both counter and pixel electrodes are made of a transparent conductor, wherein a distance between the upper and lower substrates is greater in length than a distance between the counter and pixel electrodes. (Fig. 4)

FIG. 1A
(PRIOR ART)




FIG. 1B
(PRIOR ART)




FIG.2A
(PRIOR ART)




FIG.2B
(PRIOR ART)




FIG.3




FIG.4




FIG.5A




FIG.5B




FIG.5C




FIG.5D




FIG. 6




FIG.7A




FIG.7B




FIG.7C




FIG.7D




FIG. 7E




FIG. 7F





FIG.8



Docket:

COMBINED DECLARATION AND POWER OF ATTORNEY(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT, SUPPLEMENTAL, DIVISIONAL,
CONTINUATION OR CIP)

As a below named inventor, I hereby declare that:

TYPE OF DECLARATION

This declaration is of the following type: (check one applicable item below)

- ☒ original
☐ design
☐ supplemental

Note: If the Declaration is for an International Application being filed as a divisional, continuation or continuation-in-part application, do not check next item; check appropriate one of last three items.

- ☐ national stage of PCT

Note: If one of the following 3 items apply, then complete and also attach **ADDED PAGES FOR DIVISIONAL, CONTINUATION OR CIP.**

- ☐ divisional
☐ continuation
☐ continuation-in-part (CIP)

INVENTORSHIP IDENTIFICATION

WARNING: If the inventors are each not the inventors of all the claims, an explanation of the facts, including the ownership of all the claims at the time the last claimed invention was made, should be submitted.

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

TITLE OF INVENTION

REFLECTIVE LIQUID CRYSTAL DISPLAY OF HIGH APERTURE RATIO, HIGH TRANSMITTANCE
 AND WIDE VIEWING ANGLE

SPECIFICATION IDENTIFICATION

the specification of which: (complete (a), (b) or (c))

- ☒ (a) is attached hereto.

- ☐ (b) was filed on _____ as ☐ Serial No. _____ or ☐ Express Mail No. (as Serial No. not yet known) _____ and was amended on _____ (if applicable).

Note: Amendments filed after the original papers are deposited with the PTO that contain new matter are not accorded a filing date by being referred to in the Declaration. Accordingly, the amendments involved are those filed with the application papers or, in the case of a supplemental Declaration, are those amendments claiming matter not encompassed in the original statement of invention or claims. See 37 CFR 1.67.

- ☐ (c) was described and claimed in PCT International Application No. _____ filed on _____ and as amended under PCT Article 19 on _____ (if any).

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, § 1.56,

(also check the following items, if desired)

- ☐ and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable Examiner would consider it important in deciding whether to allow the application to issue as a patent, and
- ☐ in compliance with this duty, there is attached an information disclosure statement, in accordance with 37 CFR 1.98.

PRIORITY CLAIM (35 U.S.C. § 119(a)-(d))

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

(complete (d) or (e))

- ☐ (d) no such applications have been filed.
- ☒ (e) such applications have been filed as follows.

Note: Where item (c) is entered above and the international application which designated the U.S. itself claimed priority check item (e), enter the details below and make the priority claim.

PRIOR FOREIGN/PCT APPLICATION(S) FILED WITHIN 12 MONTHS (6 MONTHS FOR DESIGN) PRIOR TO THIS APPLICATION AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. § 119(a)-(d)

COUNTRY (OR INDICATE IF PCT)	APPLICATION NUMBER	DATE OF FILING (day/month/year)	PRIORITY CLAIMED UNDER 35 USC 119	
Republic of Korea	98-25783	30/06/1998	<input checked="" type="checkbox"/> YES	NO <input type="checkbox"/>
			<input type="checkbox"/> YES	NO <input type="checkbox"/>
			<input type="checkbox"/> YES	NO <input type="checkbox"/>
			<input type="checkbox"/> YES	NO <input type="checkbox"/>
			<input type="checkbox"/> YES	NO <input type="checkbox"/>

**CLAIM FOR BENEFIT OF PRIOR U.S. PROVISIONAL APPLICATION(S)
(34 U.S.C. § 119(e))**

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

PROVISIONAL APPLICATION NUMBER	FILING DATE

**ALL FOREIGN APPLICATION(S), IF ANY, FILED MORE THAN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION**

Note: If the application filed more than 12 months from the filing date of this application is a PCT filing forming the basis for this application entering the United States as (1) the national stage or (2) a continuation, divisional, or continuation-in-part, then also complete ADDED PAGES TO COMBINED DECLARATION AND POWER OF ATTORNEY FOR DIVISIONAL, CONTINUATION OR CIP APPLICATION for benefit of the prior U.S. or PCT application(s) under 35 U.S.C. § 120.

POWER OF ATTORNEY

I hereby appoint the following practitioner(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (*list name and registration number*).

Thomas F. Peterson, 24790; Richard J. Streit, 25765; Timothy J. Keefer, 35567; Lawrence J. Chapa, 39135; Dennis K. Scheer, Reg. 39356; Paul B. West, 18947; Joseph H. Handelman, 26179; Peter D. Galloway 27885; John Richards, 31503; Iain C. Baillie, 24090; Richard P. Berg, 28145

- ☐ Attached, as part of this declaration and power of attorney, is the authorization of the above-named practitioner(s) to accept and follow instructions from my representative(s).

SEND CORRESPONDENCE TO:

Thomas F. Peterson
c/o Ladas & Parry
224 South Michigan Avenue
Chicago, Illinois 60604

DIRECT TELEPHONE CALLS TO:
(*Name and telephone number*)

(312) 427-1300

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

Note: Carefully indicate the family (or last) name, as it should appear on the filing receipt and all other documents.

Full name of sole or first inventor

In Cheol _____ Park _____
(Given Name) (Middle Initial or Name) (Family (or Last) Name)
Inventor's signature _____
Date 06/23/1999 Country of Citizenship Republic of Korea
Residence Seoul
Post Office Address 22/1, 672-31, Panghak 1-dong, Tobong-gu, Seoul, Korea

Full name of second joint inventor, if any

Seung Hee _____ Lee _____
(Given Name) (Middle Initial or Name) (Family (or Last) Name)
Inventor's signature _____
Date June 23, 1999 Country of Citizenship Republic of Korea
Residence Kyungki-do
Post Office Address 102-1206, Hyundai Apt., 49-1, Changjeon-dong, Ich'on,
Kyungki-do, Korea

Full name of third joint inventor, if any

Bong Gyu _____ Rho _____
(Given Name) (Middle Initial or Name) (Family (or Last) Name)
Inventor's signature _____
Date June 23, 1999 Country of Citizenship Republic of Korea
Residence Kyungki-do
Post Office Address 407-16, Younghwa-dong, Changan-gu, Suwon, Kyungki-do, Korea

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

APPLICANT: In Cheol PARK et al)
)
 SERIAL NO:) Group Art Unit:
)
 FILING DATE:) Examiner:
)
 TITLE: REFLECTIVE LIQUID CRYSTAL DISPLAY OF)
 HIGH APERTURE RATIO, HIGH)
 TRANSMITTANCE AND WIDE VIEWING ANGLE)

The Assistant Commissioner for Patents
 Washington, D.C. 20231

APPOINTMENT OF ASSOCIATE ATTORNEY

Dear Sir:

The undersigned Attorney for Applicant in the above identified application for Letters Patent, hereby appoints individually and collectively as my Associate Attorneys, to prosecute this application, to make alterations and amendments therein and to transact all business in the Patent & Trademark Office connected therewith:

Douglas S. Rupert, Reg. 44434
 Steven L. Schmid, Reg. 39358

c/o Ladas & Parry
 224 South Michigan Avenue
 Chicago, Illinois 60604
 (312) 427-1300

June 30, 1999
 Date


 Attorney for Applicant

Richard J. Streit, Reg. 25765
 c/o Ladas & Parry
 224 South Michigan Avenue
 Chicago, Illinois 60604
 (312) 427-1300